



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SDL

G-Snack Design Twelve (XII) Master - SDL

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	SDL
DIMENSIONS H x W x D (mm)	1830* x 1290 x 900
WEIGHT (NET - Standard machine without options)	410 Kg
NO. OF SELECTIONS PER SHELF	12 (6 + 6)
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 96
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CONSUMPTION	227 wh/h **

* With adjustable feet

** 25°C RT - 65% H

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- 7TH SHELF
- FRONT GLASS PROTECTION
- LOCK PROTECTION
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR
- CO2 COOLING UNIT AVAILABLE



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SDX

G-Snack Design Ten (X) Master - SDX

TECHNICAL SPECIFICATIONS

	SDX
DIMENSIONS H x W x D (mm)	1830* x 1125 x 845
WEIGHT (NET - Standard machine without options)	340 Kg
NO. OF SELECTIONS PER SHELF	10
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 70
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CONSUMPTION	244 wh/h

* With adjustable feet

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- 7TH SHELF
- FRONT GLASS PROTECTION
- LOCK PROTECTION
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR
- CO2 COOLING UNIT AVAILABLE



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SC8

G-Snack Design Eight (VIII) Master - SC8

TECHNICAL SPECIFICATIONS

	SC8
DIMENSIONS H x W x D (mm)	1830* x 980 x 845
WEIGHT (NET - Standard machine without options)	310 Kg
NO. OF SELECTIONS PER SHELF	8
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 56
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	600 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CONSUMPTION	203 wh/h

* With adjustable feet

*** The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- 7TH SHELF
- FRONT GLASS PROTECTION
- LOCK PROTECTION
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR



Snacking, Solved!

An evolutionary snack machine presented with a new look. A spacious and brightly illuminated showcase enhances the product display. An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system. New software features of shelf detection and secure vending system make the machine complete.

SC6

G-Snack Design Six (VI) Master - SC6

TECHNICAL SPECIFICATIONS

	SC6
DIMENSIONS H x W x D (mm)	1830* x 830 x 845
WEIGHT (NET - Standard machine without options)	275 Kg
NO. OF SELECTIONS PER SHELF	6
NO. OF SHELVES	Standard 6 / Max. 7
NO. OF SELECTIONS	Max. 42
PROTOCOL	Executive / MDB
COOLING SYSTEM CONTROL	Electronic
INTERNAL TEMPERATURE RANGE	+2°C up to +18°C
MAX. POWER CONSUMPTION	550 W
POWER SUPPLY	230 V / 50 Hz
CLIMATE CLASS	ST (+16°C up to +38°C)
ENERGY CONSUMPTION	200 wh/h

* With adjustable feet

OPTIONAL

- SPEEDY LIFT
- DUO SYNCHRO SPIRAL (NEW)
- DOUBLE SPIRAL MOTOR
- DUO DIVIDER
- KIT SANDWICH / BAGUETTE
- 7TH SHELF
- FRONT GLASS PROTECTION
- LOCK PROTECTION
- WALL/FLOOR FIXING KIT
- SPECIAL CODED LOCK (RIELDA)
- SECURITY CASH BOX SYSTEM
- BRANDING
- CUSTOMIZED CABINET COLOUR