



Hydro-lution

The evolution of G-Drink never ends. The most successful Glass Front Vendor of our history presented in a new look. A spacious and brightly illuminated showcase enhances the product visibility. An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system.

DV9

G-Drink Design DV9 Vertical

TECHNICAL SPECIFICATIONS

| | DV9 |
|---|-----------------------|
| DIMENSIONS H x W x D (mm) | 1830* x 1215 x 845 |
| WEIGHT (NET - Standard machine without options) | 345 Kg |
| NO. OF SELECTIONS PER SHELF | 9 |
| NO. OF SHELVES | Standard 5 / Max. 7 |
| NO. OF SELECTIONS | Standard 45 / Max. 63 |
| MAX. CAPACITY (0.33 l CANS) | 504 |
| MAX. CAPACITY (0.50 l PET BOTTLES) | 360 |
| PROTOCOL | Executive / MDB |
| COOLING SYSTEM CONTROL | Electronic |
| INTERNAL TEMPERATURE RANGE | +2°C up to +10°C |
| MAX. POWER CONSUMPTION | 800 W |
| POWER SUPPLY | 230 V / 50 Hz |
| CLIMATE CLASS | N (+16°C up to +32°C) |
| ENERGY CONSUMPTION | 238 wh/h |

* With adjustable leveling screw

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- CUSTOMIZED CABINET COLOUR
- SPECIAL CODED LOCK (RIELDA)
- ANTI-VANDALISM KEY PAD AND SAFETY COIN INSERT
- WALL/FLOOR FIXING KIT
- LOCK PROTECTION
- FRONT GLASS PROTECTION
- PRODUCT SPACERS
- VARIOUS FITTING KITS
- BRANDING
- SECURITY CASH BOX SYSTEM
- CO2 COOLING UNIT AVAILABLE



Hydro-lution

The evolution of G-Drink never ends. The most successful Glass Front Vendor of our history presented in a new look. A spacious and brightly illuminated showcase enhances the product visibility. An innovative capacitive key pad with back lit numerals provide high visibility in light and dark places. New user friendly features offer a large display in blue characters with a new easy door latching system.

DC6

G-Drink Design DC6 Vertical

TECHNICAL SPECIFICATIONS

| | DC6 |
|---|-----------------------|
| DIMENSIONS H x W x D (mm) | 1830* x 940 x 845 |
| WEIGHT (NET - Standard machine without options) | 295 Kg |
| NO. OF SELECTIONS PER SHELF | 6 |
| NO. OF SHELVES | Standard 5 / Max. 7 |
| NO. OF SELECTIONS | Standard 30 / Max. 42 |
| MAX. CAPACITY (0.33 l CANS) | 336 |
| MAX. CAPACITY (0.50 l PET BOTTLES) | 240 |
| PROTOCOL | Executive / MDB |
| COOLING SYSTEM CONTROL | Electronic |
| INTERNAL TEMPERATURE RANGE | +2°C up to +10°C |
| MAX. POWER CONSUMPTION | 800 W |
| POWER SUPPLY | 230 V / 50 Hz |
| CLIMATE CLASS | N (+16°C up to +32°C) |
| ENERGY CONSUMPTION | 252 wh/h |

* With adjustable leveling screw

The Equipment contains fluorinated greenhouse gases. The fluorinated greenhouse gases are contained in hermetically sealed equipment

OPTIONAL

- CUSTOMIZED CABINET COLOUR
- SPECIAL CODED LOCK (RIELDA)
- ANTI-VANDALISM KEY PAD AND SAFETY COIN INSERT
- WALL/FLOOR FIXING KIT
- LOCK PROTECTION
- FRONT GLASS PROTECTION
- PRODUCT SPACERS
- VARIOUS FITTING KITS
- BRANDING
- SECURITY CASH BOX SYSTEM
- CO2 COOLING UNIT AVAILABLE